MODULARM ACCESSORIES

Products for Expanding System Capabilities



All Modularm systems offer audible and visual on-premise alarms and also provide remote notification capability. To facilitate remote annunciation, the following accessories are offered:

AUTOMATIC TELEPHONE DIALER

For off-premise alarm annunciation without the monthly monitoring fee of a central station.

- Turn-key system for remote notification.
- Works with existing phone line or a dedicated phone line.
- Easy installation. Requires standard 120VAC outlet, phone jack and connection to alarm.
- Completely solid state
- Field programmable with up to four telephone numbers to voice/pager operation.
- Field programmable outgoing voice message (16 seconds max.)
- Tone/Pulse dialing.
- Rechargeable battery backup with recharging circuitry for power failure operation.
- · Painted steel enclosure.
- Dimensions: 12" x 12" x 3". Weight: 11 lbs.



ILLUMINATED PUSH BUTTON FOR PANIC (ENTRAPMENT) ALARM



IP-1 provides light control, panic, and auto panic inside the compartment. Low voltage pilot light inside the compartment.

DAC-55, DL-35, 75LC, DATALARM



IP-2

IP-2 provides entrapment alarms. Low voltage pilot light inside the compartment. *MOD75, MOD24*

MD-1


The MD-1[™] adds hands free occupancy detection to your walk in. Connected through low voltage wiring to your 75LC multi-monitor[™]. The MD-1[™] will turn on and maintain your lights for the duration of your stay in the walk in using the lighting control feature provided by the 75LC multi-monitor[™]. Adding the MD-1[™] will increase safety by activating hands free Auto-panic[™]. No reprogramming needed, the 75LC multi-monitor's[™] Auto-detect[™] will pickup a connected MD-1[™] and reprogram itself for the most common settings. The MD-1 comes mounted on a standard 4X2 plate, so installation is simplified.



- **Sensing Range:** 2.5' << 40'.
- MAX current draw: 9mA
- Operating temperature: (-) 20°F << (+) 122°F
- Physical Dimensions: Motion detector 3-1/4"h x 2"w x 1-1/2"d

Mounting plate 4"w x 2"h

Mounting box 4"w x 2'h x 2-1/2"d



This document contains confidential information. The dissemination, publication, copying, or duplication of this document or the software described herein without prior written authorization is strictly prohibited.

MODULARM Accessories

Products for Expanding System Capabilities



Food Automation - Service Techniques, Inc. 905 Honeyspot Road, Stratford, CT 06615-7147 USA

Phone: +1-203-377-4414 Sales: 1-800-FASTRON Fax: **+1-203-377-8187** www.KitchenBrains.com

Toll-free technical support from the U.S., Canada, and Caribbean: 1-866-840-4271 Europe, Middle East, Africa

31 Saffron Court Southfields Business Park Basildon, Essex SS15 6SS ENGLAND Phone: +44 0 1268544000

China 1803, 18F, No 922 Hengshan Rd Shanghai 200030, CHINA Phone: **+8613916 854 613**

Asia Pacific

13A MacKenzie Road 228676 Singapore Phone: +65 98315927

This document contains confidential information. The dissemination, publication, copying, or duplication of this document or the software described herein without prior written authorization is strictly prohibited.